

You need your outreach programs printed economically and effectively. RISO has the answer to your prayers.

“Peak Printing” Patterns

Churches and religious organizations have unique and demanding office needs. Among those oddities is the fact that much of their printing is based on fundraising campaigns, monthly newsletters, envelope printing, all of which come in bunches. While toner devices work best when equal amounts of copies are printed on a daily basis, non-profit groups will instead print large amounts in a short period of time, given their unique communications requirements.

The people who print our bank statements, credit card statements or home internet invoices have similar challenges - as everything is printed and sent out on the last or first two days of the billing month. Twelve years ago, they moved away from toner and turned to a printing technology that is digital but uses no heat, no toner and can run at super high speeds without static electricity buildup. That technology is called Inkjet.

A Printer Designed to Print Outreach Program Materials

RISO addresses the type of “peak printing” requirements noted above with an Inkjet technology that will:

- Print church bulletins at speeds of up to 120 color pages per minute (500 double-sided, letter size bulletins in less than 9 minutes)
- Print color bulletins, hymn books or Sunday School material for a little over 1 penny per page (most toner devices hover around the 6 cent mark)
- Use no heat which yields low parts usage and cold copies that are easy to handle (fold, staple or add hole punch)
- Print offering envelopes of all sizes (even with glue on the flap!) without damaging the seal
- These same envelopes have become prime fundraising tools as RISO allows for the printing of outreach messages on the face of the envelope

Call your local RISO dealer today and learn about our FW Series RISO’s designed for Churches and Non-Profit organizations.



(Pictured: ComColor FW5230 with Scanner attachments)

Advantages

- **High Speed:** The ComColor FW5230 system is capable of full color cut sheet output up to 120 ppm.
- **Reliability:** With a duty cycle of 500,000 prints per month, the ComColor FW is a true workhorse.
- **Variety and Flexibility:** RISO’s patented FORCEJET™ technology utilizes a straight paper path that not only accommodates a wider range of media, but ensures a cold, flat, and dry output ideal for transition to finishing equipment.
- **Space & Power Savings:** A fraction of the size of similar output machines, this system’s small footprint easily fits into tight spaces. The system does not require dedicated power or HVAC considerations, as it utilizes a standard wall outlet and does not generate heat as toner-based systems do.
- **Cost Analysis:** ComColors are economical to own and run. Ask your RISO rep for a review of your printing needs, to see if inkjet makes sense for your organization.

Specifications

ComColor FW5230 Base Unit

| | | |
|---|--|--|
| Print Type | Line-type inkjet system | |
| Ink Type | Oil-based pigment ink (Cyan, Magenta, Yellow, Black) | |
| Print Resolution | Standard: 300 dpi (main scanning direction) × 300 dpi (sub-scanning direction) Fine: 300 dpi (main scanning direction) × 600 dpi (sub-scanning direction) | |
| Number of Gray Levels | For each CMYK color (11 gray levels) | |
| Data Processing Resolution | Standard: 300 dpi × 300 dpi Fine: 600 dpi × 600 dpi Line smoothing: 600 dpi × 600 dpi | |
| Warm-up Time | 2 min. 30 sec. or less (at room temperature of 23°C (73.4°F)) | |
| First Print Time ^{*1} | 5 sec. or less (A4 long-edge feed) | |
| First Copy Time ^{*1} | 7 sec. or less (A4 long-edge feed) | |
| Continuous Print Speed ^{*2*3} | A4 long-edge feed | Simplex: 120 ppm Duplex: 60 sheets/minute (120 ppm) |
| | Letter long-edge feed | Simplex: 120 ppm Duplex: 60 sheets/minute (120 ppm) |
| | A4 short-edge feed | Simplex: 90 ppm Duplex: 45 sheets/minute (90 ppm) |
| | Letter short-edge feed | Simplex: 90 ppm Duplex: 45 sheets/minute (90 ppm) |
| | B4 (JIS) short-edge feed | Simplex: 76 ppm Duplex: 34 sheets/minute (68 ppm) |
| | Legal short-edge feed | Simplex: 76 ppm Duplex: 34 sheets/minute (68 ppm) |
| | A3 short-edge feed | Simplex: 66 ppm Duplex: 32 sheets/minute (64 ppm) |
| | Ledger short-edge feed | Simplex: 65 ppm Duplex: 32 sheets/minute (64 ppm) |
| Paper Size | Standard Tray | Maximum: 340 mm × 550 mm (13 3/8" × 21 5/8") Minimum: 90 mm × 148 mm (3 9/16" × 5 27/32") |
| | Feed Tray | Maximum: 297 mm × 432 mm (11 11/16" × 17") Minimum: 182 mm × 182 mm (7 3/16" × 7 3/16") |
| Printable Area | Maximum: 310 mm × 544 mm (12 3/16" × 21 13/32") | |
| Guaranteed Print Area ^{*4} | Standard: Margin width of 5 mm (7/32") Maximum: Margin width of 3 mm (1/8") | |
| Paper Weight | Standard Tray | Simplex: 46 gsm to 210 gsm (12-lb bond to 56-lb bond) Duplex: 46 gsm to 210 gsm (12-lb bond to 56-lb bond) for A4 and Letter 46 gsm to 104 gsm (12-lb bond to 28-lb bond) for Ledger, A3, Legal, and B4 |
| | Feed Tray | Simplex: 52 gsm to 104 gsm (14-lb bond to 28-lb bond) Duplex: 52 gsm to 104 gsm (14-lb bond to 28-lb bond) |
| Paper Tray Capacity | Standard Tray | Height up to 110 mm (4 5/16") |
| | Feed Tray | Height up to 56 mm (2 3/16") (x 2 trays) |
| Output Tray Capacity | Height up to 56 mm (2 3/16") | |
| PDL (Page Description Language) | RISORINC/C IV | |
| Supported Protocols | TCP/IP, HTTP, HTTPS, DHCP, ftp, lpr, IPP, SNMP, Port 9100 (RAW port), IPv4, IPv6, IPsec | |
| Supported Operating Systems | Standard | Microsoft®: Windows Vista® (32-bit/64-bit), Windows® 7 (32-bit/64-bit), Windows® 8.1 (32-bit/64-bit), Windows® 10 (32-bit/64-bit), Windows Server® 2008 (32-bit/64-bit), Windows Server® 2008 R2 (64-bit), Windows Server® 2012 (64-bit) |
| | Optional ^{*5} | Mac: OS X 10.8 (64-bit), 10.9 (64-bit), 10.10 (64-bit), 10.11 (64-bit) Linux (compatible with PPD only) |
| Network Interface | Ethernet 1000BASE-T, 100BASE-TX, 10BASE-T | |
| Memory Capacity | 4 GB | |
| Hard Disk ^{*6} | Capacity | 500 GB |
| | Available Space | Approx. 430 GB |
| Operating System | Linux | |
| Power Source | AC 100-240 V, 10.0-5.0 A, 50-60 Hz | |
| | Max. 1,000W | |
| Power Consumption | Ready ^{*7} : 150 W or less Sleep ^{*8} : 4 W or less Stand-by: 0.5 W or less | |
| Operating Noise | Max. 65 dB (A) A4 long-edge feed (Simplex) at the maximum print speed | |
| Operating Environment | Temperature: 15°C to 30°C (59°F to 86°F) Humidity: 40% to 70% RH (non-condensing) | |
| Dimensions (W × D × H) | In use: 1,030 mm × 725 mm × 1,115 mm (40 19/32" × 28 9/16" × 43 29/32") With cover and tray closed: 775 mm × 705 mm × 970 mm (30 17/32" × 27 25/32" × 38 7/32") | |
| Weight | Approx. 135 kg (297 lb) | |
| Safety Information | IEC60950-1 compliant, Indoor, pollution degree 2 ^{*9} , At altitudes of 2,000 m or lower | |
| Required Space (W × D × H) ^{*10} | 1,305 mm × 1,215 mm × 1,115 mm (51 13/32" × 47 27/32" × 43 29/32") | |

Specifications are subject to change without notice.

 **RISO, Inc.**
800 District Avenue, Suite 390 Burlington, MA 01803-5063
<http://us.riso.com>

For more details please contact: