



## features

### Industry-Standard Compatibility

The SC7950 is a Certified Adobe PostScript™ Level 3 device, assuring the highest level of PostScript compatibility and photo quality grayscaling for optimal photo output quality.

### Customized Queue Design

The ability to create customized queues saves set-up time and ensures uniformity of frequently run jobs. An unlimited number of queues can be set up, and each can be designated as public or private.

### Flexible Scanning

Powerful push/pull scanning allows the user to choose to scan from the computer or directly on the glass platen. Images push-scanned using the glass platen can be made available to users on the network.



**RISO, Inc.**  
300 Rosewood Drive  
Danvers, MA 01923  
Tel: 800-876-RISO (ext. 501)  
[www.riso.com](http://www.riso.com)

©Copyright 2003 RISO, Inc. All rights reserved.  
No part of this document may be reproduced  
without permission of RISO, Inc. All products are  
trademarks of their respective companies.  
Specifications subject to change without notice.

Printed in USA

## specifications

<b>interface unit type</b>	External box
<b>CPU</b>	VIA C3 866MHz
<b>dimensions (w x d x h)</b>	7.87" x 11.81" x 13.23" (200 x 300 x 336 mm)
<b>power requirements</b>	100 to 125VAC, 50/60 Hz 200 to 240VAC, 50/60 Hz
<b>power consumption</b>	48W
<b>operating temperature and humidity</b>	41°F to 104°F (5°C to 40°C) with 40% to 70% (non-condensing)
<b>weight</b>	16.53 lb. (7.5 kg)
<b>available PDL (Page Description Language)</b>	Adobe PostScript 3
<b>platform support</b>	OS: Windows 98, Windows 2000, Windows ME, Windows NT 4.0, Windows XP and Mac OS 9.1 and 10 Classic Mode  Additional Software Requirements: Web Browser IE 5.0 or higher
<b>available input port (input interface)</b>	Ethernet (10BASE-T/100BASE-TX), Parallel and Serial for status monitoring
<b>software network protocol</b>	EtherTalk, TCP/IP, NetBIOS, LPR, SNMP, SMTP, HTTP, DHCP, IPP
<b>RAM</b>	64MB
<b>resident hard disk</b>	40GB
<b>resident fonts</b>	Adobe PostScript Type 1: 155 fonts TrueType: 36 fonts Multiple Master fonts: 2 fonts
<b>available output resolution</b>	400 x 400 and 600 x 600 note: the SC7950 output resolution is automatically adjusted to the RISO Printer-Duplicator's print resolution
<b>front panel features</b>	4 buttons: Stop, Start, Function and Power 3 LEDs: Ready/Data, Page Standby, and Error
<b>installable utilities</b>	RISO Console II, RISO Scan I, ATM, and Printer Driver Installer (Windows only)
<b>other printing features</b>	Overlay printing, TIFF printing, ASCII printing, JetDirect printing (Port 9100)

# SC7950

system controller

Item #MC8135