benefits

Outstanding Value

- Best price/performance in its class
- Powerful 200 MHz processor handles intensive printing tasks

Exceptional Performance

- Engine speed of 20-pages-per-minute and print time of less than 9 seconds to first page allow fast turnaround
- User-specified print resolution of up to 1200 x 1200 dpi produces crisp text and high-quality graphics

User Convenience

- Easily expandable, modular paper-handling options provide printing flexibility
- High-yield, single-element toner cartridge reduces operator intervention
- Print-and-hold function facilitates secure printing of confidential documents in a network environment
- Image Quick solution enables direct p o s e
 PDF and image printing from the web

C,

deliver >

 Bar Code Card supports more than 47 industry standard, algorithmically generated one- and two-dimensional bar codes





specifications

technology	Monochrome laser
speed	Up to 20 pages per minute Less than 9 seconds time to first page
print quality	1200 x 1200 dpi, 1200 image quality 600 x 600 dpi, 300 x 300 dpi
processor	200 MHz
memory (std/max)	16MB/272MB
connectivity	USB port, 10BaseT/100BaseTX Ethernet, One internal solutions port
	P520 supports the MarkNet™ X2000 series of external print servers
	P520 supports the MarkNet N2000 series of internal print servers
	Optional Tri-Port Adapter with RS-232/422 Serial, LocalTalk and IR Adapter ports
	Optional USB/Parallel 1284-C Interface Card
	Optional Coax/Twinax Adapter for SCS
multifunction options	M242*, M443*, M4500
compatibility	PostScript 3 emulation standard, PCL 6 emulation standard, PPDS Migration Tool
font selection	PostScript 3 emulation: 156 scalable fonts PCL 6 emulation: 84 scalable fonts, 2 bitmapped fonts PPDS Migration Tool: 39 scalable fonts, 5 bitmapped fonts
paper sizes and weights	Standard support including letter, legal, A4, A5, JIS B5, executive, folio, statement, and custom sizes from 5.5" x 8.27" to 8.5" x 14", Expanded custom sizes, 2.75" x 5" to 8.5" x 14" available with the Universally Adjustable Tray
	Plain paper, bond, envelopes, card stock, transparencies, paper labels, dual-web labels, polyester labels, and vinyl labels
	16 lb. to 47 lb. bond, Up to 125 lb. card stock
paper capacity (std/max)	350/3,850 sheets; Standard input sources: One 250-sheet tray, One 100-sheet multipurpose tray; Maximum input sources: 7 The 2 standard inputs plus 4 additional drawers (250-, 500-, and 2,000-sheet) in any combination, except only one 2,000- sheet input drawer may be used, One envelope feeder
	Output: 250 sheets Optional 250 sheet duplex unit for two-side printing
starter supplies	The RISO P520 ships with 5,000-page** starter cartridge
replacement supplies	20,000-page** high yield, Use and Return print cartridge, 20,000-page** high yield print cartridge
operating systems	Microsoft Windows 2000, Me, 98, 95, NT 4.0 or higher; UNIX, Linux and Mac OS.
size (w x d x h)/weight	15.7" x 20.2" x 13.4" (400 mm x 513 mm x 340 mm) 43.5 lb. (19.7 kg)
acoustics	51 dBA printing, 30 dBA idle
duty cycle	Up to 100,000 pages per month

*Minimum 32MB memory required **Yield is based on approximately 5% print coverage





RISO, Inc. 300 Rosewood Drive Danvers, MA 01923 Tel: 800-876-RISO (ext. 501) www.riso.com

©Copyright 2002 RISO, Inc. All rights reserved. No part of this document may be reproduced without permission of RISO, Inc. All products are trademarks of their respective companies. Specifications subject to change without notice.

U (J

print