

P620

laser printer

b e n e f i t s

High Performance

- Fast 30-page-per-minute output, with first page produced in less than 10 seconds
- Standard USB interface for easy host connections and fast, built-in Ethernet port on network models
- Bar Code Card supports more than 47 industry standard, algorithmically generated one- and two-dimensional bar codes

Versatile and Expandable

- Easily expandable, modular paper-handling options provide enhanced productivity
- Extensive range of media and memory enables printing of complex applications

Internet Connectivity

- ImageQuick solution (standard on Internet network models) supports direct PDF and image printing from the Web



P620 laser printer

specifications

technology	Monochrome laser
speed	Up to 30 pages per minute Less than 10 seconds time to first page
print quality	1200 x 1200 dpi, 1200 image quality 600 x 600 dpi, 300 x 300 dpi
processor	300 MHz
memory (std/max)	32MB/384MB
connectivity	USB port, 10BaseT/100BaseTX Ethernet, Two internal solutions ports P620 supports the MarkNet™ X2000 series of external print servers P620 supports the MarkNet N2000 series of internal print servers Optional Tri-Port Adapter with RS-232/422 Serial, LocalTalk and IR Adapter ports Optional USB/Parallel 1284-C Interface Card Optional Coax/Twinax Adapter for SCS
multifunction options	M242, M443, M4500
compatibility	PostScript 3 emulation standard, PCL 6 emulation standard PPDS Migration Tool
font selection	PostScript 3 emulation: 156 scalable fonts PCL 6 emulation: 84 scalable fonts, 2 bitmapped fonts PPDS Migration Tool: 39 scalable fonts, 5 bitmapped fonts
paper sizes and weights	Standard support including letter, legal, A4, A5, JIS B5, executive, folio, statement, and custom sizes from 5.5" x 8.27" to 8.5" x 14", Expanded custom sizes from 2.75" x 5" to 8.5" x 14" available with the Universally Adjustable Tray Plain paper, bond, envelopes, card stock, transparencies, paper labels, dual-web labels, polyester labels, and vinyl labels 16 lb. to 47 lb. bond, Up to 125 lb. card stock
paper capacity (std/max)	600/4,100 sheets; Standard input sources: One 500-sheet drawer, One 100-sheet multipurpose feeder; Maximum input sources: 7—The 2 standard inputs plus 4 additional drawers (250-, 500-, and 2,000-sheet) in any combination, except only one 2,000-sheet input drawer may be used, One envelope feeder <ul style="list-style-type: none">• Output (std/max): 500/3,000 sheets• Maximum output destinations: 11• Two 5-bin mailboxes plus the standard output bin Other configurations: Up to three 650-sheet output expanders, 1,850-sheet high capacity output stacker or the StapleSmart™ Finisher with one of the following: 650-sheet output expander, 5-bin mailbox <ul style="list-style-type: none">• Optional 500 sheet duplex unit for two-side printing
starter supplies	10,000 Use and Return print cartridge
replacement supplies	30,000-page* high yield Use and Return print cartridge, 30,000-page* high yield print cartridge
operating systems	Microsoft Windows 2000, Me, 98, 95, NT 4.0 or higher; UNIX, Linux and Mac OS.
size (w x d x h)/weight	16.5" x 20.2" x 15.9" (419 mm x 513 mm x 404 mm) 45 lb. (20.4 kg)
acoustics	51 dBA printing, 30 dBA idle
duty cycle	Up to 150,000 pages per month

*Yield is based on approximately 5% print coverage



RISO, Inc.
300 Rosewood Drive
Danvers, MA 01923
Tel: 800-876-RISO (ext. 501)
www.riso.com

©Copyright 2002 RISO, Inc. All rights reserved.
No part of this document may be reproduced
without permission of RISO, Inc. All products are
trademarks of their respective companies.
Specifications subject to change without notice.

Printed in USA



Item #MC8104