

RN2000

high-speed printer-duplicator

b e n e f i t s

Affordable Capabilities

When you're looking for speed, quality, and cost efficiency, choose the RN2000 Printer-Duplicator. All of the benefits that make RISO a world leader are available at a price that will please even the most budget conscious.

Economical Color Printing

For virtually the same cost as black and white, RN2000 color printing can greatly increase the impact of your printed materials. Choose a variety of different ink colors like red, blue, green, burgundy, teal, purple, orange, fluorescent pink, just to name a few.

Reduced Power Consumption

Environmentally friendly features like Auto Power Off and Auto Sleep modes reduce your energy costs, and the ability to print on newsprint and other recycled stocks can lower your printing costs as well.

Easy Operation

The RN2000 is the perfect Printer-Duplicator for multiple users. The large LCD User Interface Panel gives easy, step-by-step instructions to make printing a snap. Optional ISC (Integrated System Controller) Technology makes connecting to a network fast and easy; users in different offices or floors can access the RN2000 right from their desktops.



s m c n t r

features

Lowest Operating Costs

The RN2000 features the lowest operating costs of any of RISO's Printer-Duplicators, and it also operates for far less than other printing technologies. You can print as few as 15 copies to justify costs, making this the perfect Printer-Duplicator for smaller organizations and classrooms.

Precision Imaging

The RN2000 features unique precision imaging that delivers clear, crisp print results for a professional look.

Color, Speed, Flexibility, Reliability

Print in a palette of colors at 130 pages per minute, on a wide variety of paper stocks and sizes. Superior reliability and a long life make the RN2000 the perfect high-speed, low cost printer.

Large LCD User Interface Panel

Large format LCD Panel allows for large text and easy-to-follow operation throughout the printing process.



RISO, Inc.
300 Rosewood Drive
Danvers, MA 01923
Tel: 800-876-7476 (ext. 501)
www.riso.com

©Copyright 2001 RISO, Inc. All rights reserved.
No part of this document may be reproduced
without permission of RISO, Inc. All products are
trademarks of their respective companies.
Specifications subject to change without notice.

Printed in USA

specifications

processing	High-speed fully automatic digital scanning, thermal screening printing system
first copy time	Letter: approximately 20 seconds
printing speed	5 steps (60, 80, 100, 120, 130 ppm)
original size and type	From stage glass: book/sheet 2" x 3.5" to 11.75" x 16.5" (50 x 90 mm to 297 x 420 mm) In the optional ADF: 50 sheets 3.5" x 5.5" to 11.75" x 16.5" (90 x 140 mm to 297 x 420 mm)
paper size and weight	3.5" x 5.5" to 11.5" x 15.5" (90 x 140 mm to 292 x 394 mm) 13 lb. bond to 110 lb. index (46 g/m ² to 210 g/m ²)
image area	8.25" x 11.5" (210 x 290 mm)
paper capacity	1000 sheets, 20 lb. bond (75 g/m ²), feed and receive trays
preset reduction/enlargement	66%, 75%, 77%, 94%, 121%, 127%, 141%
zoom reduction/enlargement	50%-200% in 1% increments
standard features	Large-format LCD User Interface Panel, Print Speed/Density Control, Confidential Mode, Multi-up Printing (2-, 4-, 8-, 16-up), Adjustable Bound Document Center Erase, Programmed Printing, Print Job Memory Mode, Line, Photo, and Duo Mode, 4 Dot Photo Modes, Automatic Idle, Automatic/Manual Scanning Contrast Adjustment, Initial Setting Customization, Paper Size Detection, Precision Stacking Tray, Preventive Maintenance Indicator, and Energy Save: Auto Power Off/Auto Sleep
options	ISC (Integrated System Controller) Network Interface, Color Print Cylinders, SC5500 System Controller for PS II Compatibility, Automatic Document Feeder, Job Separator, Key Card Counter, and Stand
electrical	120 VAC, 60 Hz <3.0 A>
weight	209 lbs. (95 kg) (without stand)
dimensions (w x d x h)	51" x 25.4" x 41.1" (1295 x 645 x 1044 mm) (without stand)

optional system controller specifications:

CPU	SH-3 (66 MHz)
PDL	RISORINC 2/Enhanced GDI
OS	Windows 95/98, Windows NT 4.0, and Mac OS 7.5.3-9.0
input port	Parallel (IEEE 1284 A Centronics), Serial (RS-232C) for communication devices, Ethernet (10BASE-T/100BASE-TX)
memory	64MB
network protocol	TCP/IP, EtherTalk, FTP, SNMP, HTTP, DHCP
ethernet type	10BASE-T/100 BASE-T

RN2000
High-speed printer-duplicator

Item #MC8000