

RN2530

high-speed printer-duplicator

benefits

Precision Imaging and Dual Station Imaging

The RN2530 features unmatched precision imaging that delivers clear, crisp print results for a professional look. Choose the right printing station for each original: print from the desktop or place hard copy directly on the glass imaging platen.

Printing Versatility, Flexibility, and Reliability

Print in a palette of colors at 130 pages per minute, on a wide variety of paper stocks and sizes. The RN2530 offers the printing versatility that is built into every RISO Printer-Duplicator. Superior reliability and a long life make the RN2530 the perfect high-speed, low cost networkable printing solution.

Improved Image Quality

The RN2530 automatically identifies photos and text on each page, then varies the print density and contrast to produce the finest results every time. High resolution ensures superb print quality.

Printing Solutions

Create the printing system that is right for your organization! The RN2530 may be configured with an assortment of accessories, including an Edit Board, Automatic Document Feeder, Sorters, System Controllers, and more. Choose only the accessories you need, or add accessories as your organization grows.



features

Advanced Photo Processing

Automatically adjusts shadows and highlights for more professional photo reproduction.

Touch Screen

The RN2530's large-format Touch Screen is intuitively designed for fingertip control and can be used with no special training. The Touch Screen display gives complete details of all operations, consumable levels, and queued jobs.

Color Separation Software

RISO's optional Color Separation software makes it easy to separate colors from a variety of software programs.

Multi-Up Printing

Print multiple versions of namebadges, tickets, menus, and more in a single pass. Choose 2-up, 4-up, 8-up, 16-up, or tickets for the style that is right for you.



RISO, Inc.
300 Rosewood Drive
Danvers, MA 01923
Tel: 800-876-RISO (ext. 501)
www.riso.com

©Copyright 2002 RISO, Inc. All rights reserved.
No part of this document may be reproduced
without permission of RISO, Inc. All products are
trademarks of their respective companies.
Specifications subject to change without notice.

Printed in USA

specifications

processing	High-speed fully automatic digital scanning, thermal screening printing system
first copy time	Letter: approximately 16 seconds
printing speed	5 steps (60, 80, 100, 120, 130 ppm)
original size and type	From stage glass: book/sheet 2" x 3.5" to 11.625" x 17" (50 x 90 mm to 297 x 432 mm) In the optional ADF: 50 sheets 3.5" x 5.5" to 11.625" x 17" (90 x 140 mm to 297 x 432 mm)
paper size and weight	3.5" x 5.5" to 11.375" x 17" (90 x 140 mm to 290 x 432 mm) 13 lb. bond to 110 lb. index (46 g/m ² to 210 g/m ²)
image area	8.25" x 14" (210 x 357 mm)
paper capacity	1000 sheets, 20 lb. bond (75 g/m ²), feed and receive trays
preset reduction/enlargement	50%, 61%, 65%, 78%, 129%, 154%
zoom reduction/enlargement	50%-200% in 1% increments
standard features	ISC (Integrated System Controller) Technology, Large Touch Screen Panel, Dual Station Imaging, Print Speed/Density Control, Confidential Mode, Multi-up Printing, Adjustable Bound Document Center Erase, Programmed Printing, Master Renewal Mode, Print Job Memory Mode, Line, Photo, and Duo Mode, 4 Dot Photo Modes, Automatic Idle, Automatic/Manual Scanning Contrast Adjustment, Initial Setting Customization, Mirror Image Production, Precision Stacking Tray, Paper Size Detection, Preventive Maintenance Indicator, Energy Save: Auto Power Off/Auto Sleep, and Stand
options	Color Print Cylinders, System Controllers for PS II and PS III Compatibility, Network Interface Card, Document Memory Card, Sorters, Automatic Document Feeder, Edit Board, Job Separator, and Key Card Counter
electrical	120 VAC, 60 Hz <3.0 A>
weight	233 lbs. (106 kg) without stand
dimensions (w x d x h)	51" x 27.375" x 25" (1300 x 695 x 635 mm) without stand
system controller specifications:	
CPU	SH-3 (133 MHz)
PDL	RISORINC 3/Enhanced GDI
OS	Windows 95/98, Windows NT 4.0, Windows 2000, Windows XP and Mac OS 7.6.1-9.0 (excluding 8.5)*
input port	Parallel (IEEE 1284A Centronics), Serial (RS-232C) for communication devices, Ethernet (10BASE-T/100BASE-T)
memory	16MB
network protocol	NetBIOS over NetBEUI, AppleTalk, TCP/IP, EtherTalk, FTP, SNMP, HTTP, DHCP
ethernet type	10BASE-T/100 BASE-T

*Macintosh or network connection requires optional NET-B card.

RN25300
High-speed printer-duplicator

Item #MC8051