

ComColor FT 5000

Ultra High-Speed
Full-Color Inkjet Printers



ULTRA-FAST

full-color printing



A feature-rich lineup for
**NATURE-
FRIENDLY**

Full-color A4 printing



Print speed
100 ppm



Print size
A4



Full color



3 trays



Low energy
consumption



Environmental
certification

ComColor FT 5000 Specifications

Print Type		Line-type inkjet system
Ink Type		Oil-based pigment ink (Cyan, Magenta, Yellow, Black)
Print Resolution		Standard: 300 dpi (main scanning direction) × 300 dpi (sub-scanning direction) Fine: 300 dpi (main scanning direction) × 600 dpi (sub-scanning direction)
Number of Gray Levels		For each CMYK color (11 gray levels)
Data Processing Resolution		Standard: 300 dpi × 300 dpi Fine: 600 dpi × 600 dpi Line smoothing: 600 dpi × 600 dpi
Warm-up Time		2 min. 30 sec. or less (at room temperature of 73° F)
First Print Time *1		5 sec. or less (A4)
Continuous Print Speed *2	A4	Simplex: 100 ppm Duplex: 50 sheets/minute (100 ppm)
Paper Size	Standard Tray	Maximum: 13.39 inch x 21.65 inch *3 Minimum: 3.4 inch x 5.83 inch
	Feed Tray	Maximum: 11.69 inch x 17 inch Minimum: 17.16 inch × 7.16 inch
Printable Area		Maximum: 8.27 inch × 21.42 inch
Guaranteed Print Area *4		Standard: Margin width of 0.19 inch Maximum: Margin width of 0.12 inch
Paper Weight	Standard Tray	Simplex: 46 gsm to 210 gsm *5 Duplex: 46 gsm to 210 gsm *5 for A4/46 gsm to 104 gsm for A3, B4 (JIS)
	Feed Tray	Simplex/Duplex: 52 gsm to 104 gsm
Paper Tray Capacity	Standard Tray	Height up to 4.33 inch
	Feed Tray	Height up to 2.2 inch (2 trays)
Output Tray Capacity		Height up to 2.2 inch
Page Description Language		RISORINC/C IV
Supported Protocols		TCP/IP, HTTP, HTTPS (TLS), DHCP, FTP, LPR, IPP, SNMP (SNMP v1), Port 9100 (RAW port), IPv4, IPv6, IPSec (IKEv1)
Supported Operating Systems	Standard	Microsoft®: Windows®, Windows Server® *6
	Optional *7	Mac: macOS *6 Linux®: Compatible with PPD only
Network Interface		Ethernet 1000BASE-T/100BASE-TX/10BASE-T×2 Channel
Memory Capacity		4 GB
Hard Disk *8	Capacity	500 GB
	Available Space	Approx. 430 GB
Operating System		Linux
Power Source		AC 100-240 V, 10.0-5.0 A, 50-60 Hz
Power Consumption		Max. 1,000 W Ready *9: 95 W or less Sleep *10: 2 W or less Stand-by: 0.4 W or less
Operating Noise		64dB (A) or less at printing
Operating Environment		Temperature: 59° F to 86° F Humidity: 40% to 70% RH (non-condensing)
Dimensions (W x D x H)		In use: 40 inch x 28.93 inch x 43.90 inch With cover and tray closed: 30.51 inch × 27.95 inch × 38.19 inch
Weight		Approx. 300 lbs.
Dimensions When Operating (W x D x H)		With the front cover open and the operation panel in the upright position: 46.65 inch × 48.23 inch × 43.90 inch
Accessories		Scanner HS7000, Face Down Finisher F10, Multifunction Finisher FG20/Folder Unit FG20, Auto-Control Stacking Tray II, Wide Stacking Tray, ComColorExpress RS1200C, PS Kit FG10, IC Card Authentication Kit II, Envelope Feed Kit, Card Feed Kit

Specifications are subject to change without notice.

*1 Within 10 minutes after the last print job.

*2 When using plain paper and recycled paper (85 gsm), and standard density setting. Chart used: Print measurement pattern [Color measurement sample 2 (JEITA standard pattern J6)].
The continuous print speed varies depending on the type of optional output equipment connected.
Face Down Finisher: Without offset: 100 sheets/minute (A4 Simplex), Offset output: 82 sheets/minute (A4 Simplex).

*3 When using duplex print: 13.39 inch × 18.11 inch.

*4 The guaranteed area when printing images is the area enclosed within 0.19 inch of the edges of the paper. The margin when printing envelopes is 0.39 inch.

*5 Duplex printing is not guaranteed with thick paper the weight of which is greater than 104 gsm.

*6 For the OS version, please refer to the RISO Website or contact your local sales representative.

*7 Optional PS Kit FG10 or ComColor Express RS1200C is required.

*8 One gigabyte (GB) is calculated as 1 billion bytes.

*9 Without printing and temperature adjustment operation.

*10 When setting [Power Consumption (in sleep)] to [Low].



ComColor FT Ink Cartridges

Colors: Black, Cyan, Magenta, Yellow

Environmental Certifications



RISO and ComColor are trademarks or registered trademarks of RISO KAGAKU CORPORATION. Mac and macOS are trademarks of Apple Inc. Microsoft, Windows, and Windows Server are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Linux® is the registered trademark of Linus Torvalds in the U.S. and other countries. Other corporate names and/or trademarks are either registered trademarks or trademarks of each company, respectively.



RISO Inc.
10 State Street, Suite 201
Woburn, MA 01801
us.riso.com