

G912

color laser printer

benefits

Performance

- Up to 28ppm monochrome and color quickly handles short or long run jobs to maximize productivity
- 600 MHZ RISC processor with 256MB of RAM quickly processes large wide-format color jobs

Cost Effective

- Three levels of toner saver saves up to 50% of toner usage monochrome or color
- Fast color speed and wide format capability deliver high value for a reasonable price

Print Quality

- 2400 Image Quality standard provides color images and business graphics without having to pay extra

- SWOP simulated and EuroScale simulated color tables with Pantone Calibration provides accurate color for pre-press layouts and finished collaterals

Versatility

- Production paper handling with maximum input of 5300 sheets and output of 1650 sheets. Stapling, hole punching, and job offset allows users to professionally finish documents close to their workstation.
- 100,000 page maximum monthly duty cycle allows large workgroup support and production printing capability in one device.
- Wide format capability extends the company's in house printing capability enabling quicker turn around of critical print jobs and enhancing security



Supported Operating Systems

Apple

- Apple Mac OS 8.6 - 9.x
- Apple Mac OS X

Microsoft Windows

- Microsoft Windows 2000 (Professional/Server/Advanced Server)
- Microsoft Windows 95 4.00.950 or later
- Microsoft Windows 98 (2nd edition)
- Microsoft Windows Me
- Microsoft Windows NT (4.00/4.00 Server)
- Microsoft Windows XP (Home, Professional)

Novell

- Novell Netware Enterprise Print Services (NEPS) with Lexmark NDPS IP Gateway
- Novell NetWare® 3.x, 4.x, 5.x, 6.x including full NDS and NDPS support
- Novell® Distributed Print Services™ (NDPS™) 2.0 or later with Lexmark NDPS IP Gateway

Linux

- Red Hat Linux 7.2, 7.3, 8.0
- SuSE 7.2, 7.3, 8.0 Linux

UNIX

- Certified Solaris Ready by Sun Microsystems
- Compaq (Digital) UNIX 4.0D
- Compaq Tru64 UNIX 4.0F, 5.1
- HP-UX 10.20, 11.00
- IBM AIX 4.2.1, 4.3.3, 5.1
- SCO OpenServer 5.0.4, 5.0.5, 5.0.6
- SGI IRIX 6.5.x
- Sun Solaris 2.6, 7, 8, 9
- Sun Solaris x86 2.6, 7, 8
- (SCO) UnixWare 2.1.3, 7.1, 7.1.1

Other

- IBM iSeries or IBM AS/400® Systems with TCP/IP with OS/400® V3R1 or later using OS/400 Host Print Transform
- Virtually any platform supporting TCP/IP

Citrix MetaFrame

- Microsoft Windows 2000 Server Terminal Services, with Citrix MetaFrame 1.8 or XP 1.0
- Microsoft Windows NT 4.0 Terminal Server, with Citrix® MetaFrame® 1.8 or XP 1.0

Citrix, MetaFrame and MetaFrame XP are registered trademarks or trademarks of Citrix Systems, Inc. in the U.S. and other countries.



RISO, Inc.

300 Rosewood Drive
Danvers, MA 01923
Tel: 800-876-RISO (ext. 501)
www.riso.com

©Copyright 2003 RISO, Inc. All rights reserved. No part of this document may be reproduced without permission of RISO, Inc. All products are trademarks of their respective companies. Specifications subject to change without notice.

Printed in USA

s p e c i f i c a t i o n s

Print Technology	Color LED
Color Control	Automatic Color Correction
Print Resolution	Black, Color: 2400 Image Quality
Print Speed (letter)	Black, Color: Up to 28 pages per minute
Print Speed (A4)	Black, Color: Up to 29 pages per minute
Time to First Page	Black, Color: <15 seconds
Processor	600 MHz
Memory network model	Standard: 256 MB; Expandable Memory; Maximum: 512 MB
Paper Handling Configuration (Standard)	100-Sheet Multipurpose Feeder, 2 x 550-Sheet Drawers, 100-Sheet Exit Tray, 550-Sheet Output Bin Duplex
Paper Handling Configuration (Optional)	Heavy Media Input Tray, 2x550-Sheet Drawer with Printer Stand, 3,000-Sheet High-capacity Feeder, 1,100-Sheet Staple Punch Finisher
Media Sizes, Supported	A3 (11.69" x 16.54" or 297 x 420mm), A4 (8.27" x 11.7" or 210 x 297mm), A5 (5.83" x 8.27" or 148 x 210mm), Banner (11.69" x 36" or 286 x 914mm), Executive (7.25" x 10.5" or 184 x 267mm), JIS-B4 (10.12" x 14.33" or 257 x 364mm), JIS-B5 (7.17" x 10.12" or 182 x 257mm), Ledger (11" x 17" or 279 x 432mm), Legal (8.5" x 14" or 216 x 355mm), Letter (8.5" x 11" or 216 x 279mm), Super Tabloid (12" x 18" or 305 x 457mm), B5 Envelope (6.93" x 9.84" or 176 x 250mm), C4 Envelope (9.02" x 12.80" or 229 x 324mm), C5 Envelope (6.38" x 9.02" or 162 x 229mm), DL Envelope (4.33" x 8.66" or 110 x 220mm), 7 3/4 Envelope (3.875" x 7.5" or 98.4 x 190.5mm), 9 Envelope (3.875" x 8.9" or 98.4 x 225.4 mm), 10 Envelope (4.125" x 9.5" or 105 x 241mm)
Media Types, Supported	Card Stock, Envelopes, Glossy paper, Paper Labels, Plain Paper, Transparencies
Paper Input Capacity	Standard: 1200 pages 20 lb or 75 gsm bond Maximum: 5300 pages 20 lb or 75 gsm bond
Paper Output Capacity	Standard: 650 pages 20 lb or 75 gsm bond Maximum: 1650 pages 20 lb or 75 gsm bond
A3 Paper Input Capacity	Standard: 1200 pages 75 gsm bond Maximum: 2300 pages 75 gsm bond
A3 Paper Output Capacity	Standard: 650 pages 75 gsm bond Maximum: 1650 pages 75 gsm bond
Envelope Capacity	10
Finishing Option	Yes
Supplies Yields	14,000*-page black and color Toner Cartridges. Ships with 8,000*-page black and color Starter Toner Cartridges *Yield at approximately 5% coverage per color
Standard Ports	USB, Ethernet 10/100BaseTX, One Internal Card Slot
Optional Local Ports	Internal 1284-C Bidirectional Parallel, Internal RS-232C serial
Optional Network Ports	Internal Ethernet 10/100BaseTx, Internal Ethernet 10BaseT/2, Internal Fiber 10Basefl, Internal Fiber 100Basefx, Internal Token-Ring, External 802.11b Wireless, Coax/Twinax Adapter for SCS
Network Connectivity	Using Standard Ethernet or MarkNet Print Server
Additional Products	Bar Code Printing, Custom Business Forms, IBM Mainframe and AS/400 Printing, Internet Printing, Local Printing, Management and Installation, Network Printing, SAP Printing
Printer Languages	Standard: PCL 6 Emulation, PostScript 3 Emulation
Font Selection	156 scalable PostScript fonts, 2 PCL bitmap fonts, 84 scalable PCL fonts, Chinese and Japanese Font DIMMs for Color
Printable Area	To within 0.16" (4.0 mm) of the top, bottom, left, right edges
Size (H x W x D)	25.2" x 27.4" x 25.8" (641 x 695 x 655 mm)
Weight	217.8 lbs. (99 Kg)
Power and Electrical Specs	Nominal Input Voltage: 110V
Noise Level	Idle: 48 dBA; Operating: 58 dBA
Duty Cycle, Maximum	Based on one month usage, 100,000 pages per month

G912

color laser printer



Item #MC8200