

M630

multifunction printer

b e n e f i t s

Product Overview

The RISO M630 MFP is the perfect choice for small workgroups who need to print, fax, and scan quickly and affordably. Its powerful 35 page-per-minute engine delivers documents in a blazing fast 10 seconds. Fax and color scanning are standard features, not expensive add-ons that you find with many copier-based MFPs.

- Up to 35 ppm letter, 33 ppm A4
- Time to first page: 10 seconds
- 300 MHZ processor
- 64 MB RAM standard
- Network standard
- Single pass simplex scanner

Affordable

The RISO M630 MFP incorporates print, copy, fax and color network scan capabilities into one device at a very affordable price. The RISO M630 MFP consolidates supplies for print, copy and fax, and duplex printing and multi-up capabilities save paper. Powerful, yet affordable features are integrated into one compact multifunction device to save you money and space.

Easy to use

Now you can print complex, demanding jobs with the ease-of-use and image quality you expect in a digital device. The RISO M630 MFP has an intuitive, easy-to-use interface to increase productivity. Users seldom wait for print jobs with this high performance, 35 ppm, network multifunction solution. You can scan your documents and fax or e-mail them wherever you want, for walk-up, anytime use.



Supported Operating Systems

Apple

- Apple Mac OS 8.6 - 9.x
- Apple Mac OS X

Microsoft Windows

- Microsoft Windows 2000 (Professional/Server/Advanced Server)
- Microsoft Windows 95 4.00.950 or later
- Microsoft Windows 98 (2nd edition)
- Microsoft Windows Me
- Microsoft Windows NT (4.00/4.00 Server)
- Microsoft Windows XP (Home, Professional)

Citrix MetaFrame

- Microsoft Windows 2000 Server Terminal Services, with Citrix MetaFrame 1.8 or XP 1.0
- Microsoft Windows NT 4.0 Terminal Server, with Citrix® MetaFrame® 1.8 or XP 1.0

Citrix, MetaFrame and MetaFrame XP are registered trademarks or trademarks of Citrix Systems, Inc. in the U.S. and other countries.

Linux

- Red Hat Linux 7.2, 7.3, 8.0
- SuSE 7.2, 7.3, 8.0 Linux

UNIX

- Certified Solaris Ready by Sun Microsystems
- Compaq (Digital) UNIX 4.0D
- Compaq Tru64 UNIX 4.0F, 5.1
- HP-UX 10.20, 11.00
- IBM AIX 4.2.1, 4.3.3, 5.1
- SCO OpenServer 5.0.4, 5.0.5, 5.0.6
- SGI IRIX 6.5.x
- Sun Solaris 2.6, 7, 8, 9
- Sun Solaris x86 2.6, 7, 8
- (SCO) UnixWare 2.1.3, 7.1, 7.1.1

Novell

- Novell Netware Enterprise Print Services (NEPS) with Lexmark NDPS IP Gateway
- Novell NetWare® 3.x, 4.x, 5.x, 6.x including full NDS and NDPS support
- Novell® Distributed Print Services™ (NDPS™) 2.0 or later with Lexmark NDPS IP Gateway

Other

- IBM iSeries or IBM AS/400® Systems with TCP/IP with OS/400® V3R1 or later using OS/400 Host Print Transform
- Virtually any platform supporting TCP/IP



RISO, Inc.

300 Rosewood Drive
Danvers, MA 01923
Tel: 800-876-RISO (ext. 501)
www.riso.com

©Copyright 2003 RISO, Inc. All rights reserved. No part of this document may be reproduced without permission of RISO, Inc. All products are trademarks of their respective companies. Specifications subject to change without notice.

s p e c i f i c a t i o n s

Function	Copying, Faxing, Printing, Color Network Scanning
Print Resolution (black)	1200 x 1200 dpi, 1200 Image Quality, 600 x 600 dpi
Print Speed	Letter, black: Up to 35 pages per minute A4, black: Up to 33 pages per minute
Time to First Page (black)	<8.5 seconds
Copy Speed	Letter, black: Up to 35 pages per minute A4, black: Up to 33 pages per minute
First Copy Out Time (mono)	10 seconds
Scan Resolution	600 x 600 dpi
Scan Speed (letter/A4)	Black: Up to 15 pages per minute; Color: Up to 14 pages per minute
Processor	300 MHz
Memory MFP	Standard: 64 MB; Maximum: 288 MB
Modem Speed	33.6 Kbps
Scan Area	Maximum: 8.5 x 14 inches (216 x 355 mm)
ADF Original Input Capacity	Up to 25 pages 20 lb or 75 gsm bond
ADF Media Weight	Maximum: 32 lbs. (120 gsm)
Reduce/Enlarge Range	50 to 200 %
Fax Server Integration	Biscom FAXCOM, Equisys ZetaFax, Omtool Fax Sr., Captaris RightFax
Scan to File	Scan to FTP server, e-mail, PC
Document Scanning & Distribution	RISO Document Solutions Suite
Standard Ports	USB, Centronics IEEE 1284 Bidirectional Parallel, Ethernet 10/100BaseTX
Optional Local Ports	External RS-422 serial
Optional Network Ports	External 802.11b Wireless
Network Connectivity	Using Standard Ethernet or MarkNet Print Server
Paper Handling Configuration (Standard)	100-Sheet Multipurpose Feeder, 250-Sheet Input Tray, 250-Sheet Output Bin
Paper Handling Configuration (Optional)	500-Sheet Drawer, 250-Sheet Drawer, 2,000-Sheet Drawer, 250-Sheet Duplex Unit, Envelope Feeder. Optional furniture required.
Paper Input Capacity	Standard: 350 pages 20 lb or 75 gsm bond Maximum: 2350 pages 20 lb or 75 gsm bond
Paper Output Capacity	Standard: 250 pages 20 lb or 75 gsm bond
Size (H x W x D)	MFP bundle: 27.6 x 20 x 23" (701 x 508 x 584 mm)
Weight	MFP bundle: 52.1 lbs. (23.6 Kg)
Noise Levels	Idle: 31 dBA; Copying: 62 dBA; Printing: 53 dBA; Scanning: 60 dBA
Engine Duty Cycle	Maximum: 175,000 pages per month
Scanner Duty Cycle	Maximum: 4,000 pages per month
Certifications	FCC Class A, UL 60950, CSA, ICES Class A, CS03, IEC 320-1

M630

multifunction printer

