benefits

Product Overview

The RISO M634 is a full-featured MFP that can help you effectively tackle all of your document-based business needs. With its fast, 45 page-per-minute engine, even the most graphic-intense documents are delivered on time. Fax and color scanning are standard features, not expensive addons that you find with many copier-based MFPs. Add optional duplex and finishing and see how productive the RISO M634 MFP can make your organization.

- Up to 45 ppm letter, 43 ppm A4
- Time to first page: <8.5 seconds
- 500 MHZ processor
- 144 MB RAM standard
- Network standard
- Single pass duplex scanner

Large-Format Touch Screen

The RISO M634 MFP utilizes an intuitive touch-screen interface for easy navigation of printing, copying, faxing and scanning features. The large-format color touch-screen has a built-in user manual to provide on-the-spot reference for advanced functions.

Security Built In

The RISO M634 MFP features a built-in ose corporate security option to prevent unsolicited scanned emails to anyone in your organization. With this feature enabled, users must log into the network through the color touch-screen to utilize the scanning features, which will automatically add the user's email address.

Save Money with Scanning

Scan directly to email and all but eliminate long distance fax charges! The RISO M634 adds easy-to-use color scanning features to your workplace. Its intuitive touch-screen lets you search for email addresses in an on-line corporate directory or manually enter an address, subject and message.



Supported Operating Systems

Apple

- Apple Mac OS 8.6 9.x
- Apple Mac OS X

Microsoft Windows

- Microsoft Windows 2000 (Professional/Server/ Advanced Server)
- Microsoft Windows 95 4.00.950 or later
- Microsoft Windows 98 (2nd edition)
- Microsoft Windows Me
- Microsoft Windows NT (4.00/4.00 Server)
- Microsoft Windows XP (Home, Professional)

Citrix MetaFrame

- Microsoft Windows 2000 Server Terminal Services, with Citrix MetaFrame 1.8 or XP 1.0
- Microsoft Windows NT 4.0 Terminal Server, with Citrix®MetaFrame® 1.8 or XP 1.0

Citrix, MetaFrame and MetaFrame XP are registered trademarks or trademarks of Citrix Systems, Inc. in the U.S. and other countries.

Linux

- Red Hat Linux 7.2, 7.3, 8.0
- SuSE 7.2, 7.3, 8.0 Linux

LINIX

- Certified Solaris Ready by Sun Microsystems
- Compaq (Digital) UNIX 4.0D
- Compaq Tru64 UNIX 4.0F, 5.1
- HP-UX 10.20, 11.00
- IBM AIX 4.2.1, 4.3.3, 5.1
- SCO OpenServer 5.0.4, 5.0.5, 5.0.6
- SGI IRIX 6.5.x
- Sun Solaris 2.6, 7, 8, 9
- Sun Solaris x86 2.6, 7, 8
- (SCO) UnixWare 2.1.3, 7.1, 7.1.1

Novell

- Novell Netware Enterprise Print Services (NEPS) with Lexmark NDPS IP Gateway
- Novell NetWare® 3.x, 4.x, 5.x, 6.x including full NDS and NDPS support
- Novell® Distributed Print Services™ (NDPS™) 2.0 or later with Lexmark NDPS IP Gateway

Other

- IBM iSeries or IBM AS/400° Systems with TCP/IP with OS/400° V3R1 or later using OS/400 Host Print Transform
- Virtually any platform supporting TCP/IP



RISO, Inc.

300 Rosewood Drive Danvers, MA 01923 Tel: 800-876-RISO (ext. 501) www.riso.com

©Copyright 2003 RISO, Inc. All rights reserved. No part of this document may be reproduced without permission of RISO, Inc. All products are trademarks of their respective companies.

Specifications subject to change without notice.

specifications

Function Copying, Faxing, Printing, Color Network Scanning
Print Resolution (black) 1200 x 1200 dpi, 1200 Image Quality, 600 x 600 dpi

Print Speed Letter, black: Up to 45 pages per minute
A4, black: Up to 43 pages per minute

Time to First Page (black) <8.5 seconds

Copy Speed Letter, black: Up to 45 pages per minute

A4, black: Up to 43 pages per minute

First Copy Out Time (mono) 10.5 seconds

Scan Resolution 300 x 300 dpi /Single Pass Duplex Scanner

Scan Speed (letter/A4) Black: Up to 23 pages per minute;

Color: Up to 14 pages per minute

Processor 500 MHz

Memory MFP Standard: 144 MB; Maximum: 336 MB

Modem Speed 33.6 Kbps

Scan Area Maximum: 8.5 x 14 inches (216 x 355 mm)

ADF Original Input Capacity Up to 50 pages 20 lb or 75 gsm bond

ADF Media Weight Maximum: 32 lbs. (120 gsm)
Copy Quantity 1 to 999 copies at one time

Reduce/Enlarge Range 25 to 400 %

Fax Server Integration Biscom FAXCOM, Equisys ZetaFax, Omtool Fax Sr., Captaris

RightFax

Scan to File Scan to FTP server, e-mail, PC

Document Scanning RISO Document Solutions Suite

& Distribution

Standard Ports USB, Ethernet 10/100BaseTX, Two Internal Card Slots

Optional Local Ports Internal RS-232C serial

Optional Network Ports External 802.11b Wireless, Coax/Twinax Adapter for SCS

Network Connectivity Using Standard Ethernet

Paper Handling 100-Sheet Multipurpose Feeder, 500-Sheet Input Tray,

Configuration (Standard) 500-Sheet Output Bin

Paper Handling
Configuration (Optional)
500-Sheet Drawer, 250-Sheet Drawer, 2,000-Sheet Drawer, 250-Sheet Duplex Unit, Envelope Feeder. Optional furniture.

Paper Input Capacity Standard: 600 pages 20 lb or 75 gsm bond Maximum: 4100 pages 20 lb or 75 gsm bond

Paper Output Capacity Standard: 500 pages 20 lb or 75 gsm bond

Size (H x W x D) MFP bundle: 32 x 22.5 x 21.5" (813 x 572 x 546 mm)

Weight MFP bundle: 77.5 lbs. (35.2 Kg)

Noise Levels Idle: 39 dBA; Copying: 58 dBA; Printing: 53 dBA;

Scanning: 53.1 dBA

Engine Duty Cycle Maximum: 225,000 pages per month
Scanner Duty Cycle Maximum: 10,000 pages per month

Certifications FCC Class A, UL 60950, CSA, ICES Class A, CS03, IEC 320-1





Item #MC8199