

M752

multi-function printer

benefits

High Value

The RISO M752 MFP is the only MFP you'll need for all your office needs! This one MFP provides both color and mono printing with no cost penalty for printing in black and white.

High Performance

The M752 produces a first color print in less than 17.5 seconds so that users can get short jobs printed in a hurry. Plus, the 600 MHz RISC processor with 256MB of RAM quickly processes large complex color jobs.

Excellent Quality

With true 1200 x 1200 dpi and 2400 Image Quality, the M752 provides vibrant color prints and business graphics.

Flexible and Easy to Use

The RISO M752 MFP uses a customizable touch-screen interface bringing simplicity and industry-specific tailored solutions to enterprise customers. When used with the RISO Document Solutions Suite software, the M752 offers flexible solutions for electronic forms creation and merge, document capture and electronic distribution, and on-demand document retrieval and printing.



supported operating systems

Apple

- Apple Mac OS 8.6 - 9.x
- Apple Mac OS X

Microsoft Windows

- Microsoft Windows 2000 (Professional/Server/Advanced Server)
- Microsoft Windows 95 4.00.950 or later
- Microsoft Windows 98 (2nd edition)
- Microsoft Windows Me
- Microsoft Windows NT (4.00/4.00 Server)
- Microsoft Windows Server 2003

Citrix MetaFrame

- Microsoft Windows 2000 Server Terminal Services, with Citrix MetaFrame 1.8 or XP 1.0
 - Microsoft Windows NT 4.0 Terminal Server, with Citrix® MetaFrame® 1.8 or XP 1.0
- Citrix, MetaFrame and MetaFrame XP are registered trademarks or trademarks of Citrix Systems, Inc. in the U.S. and other countries.

Linux

- Red Hat Linux 7.2, 7.3, 8.0
- SuSE 7.2, 7.3, 8.0 Linux

UNIX

- Compaq (Digital) UNIX 4.0D
- Compaq Tru64 UNIX 4.0F, 5.1
- HP-UX 10.20, 11.00
- IBM AIX 4.2.1, 4.3.3, 5.1
- SCO OpenServer 5.0.4, 5.0.5, 5.0.6
- SGI IRIX 6.5.x
- Sun Solaris 2.6, 7, 8, 9
- Sun Solaris x86 2.6, 7, 8
- (SCO) UnixWare 2.1.3, 7.1, 7.1.1

Novell

- Novell Netware Enterprise Print Services (NEPS) with Lexmark NDPS IP Gateway
- Novell NetWare® 3.x, 4.x, 5.x, 6.x including full NDS and NDPS support
 - Novell® Distributed Print Services™ (NDPS™) 2.0 or later with Lexmark NDPS IP Gateway

Other

- IBM iSeries or IBM AS/400® Systems with TCP/IP with OS/400® V3R1 or later using OS/400 Host Print Transform
- Virtually any platform supporting TCP/IP



RISO, Inc.

300 Rosewood Drive
Danvers, MA 01923
Tel: 800-876-RISO (ext. 501)
www.riso.com

©Copyright 2004 RISO, Inc. All rights reserved.
No part of this document may be reproduced
without permission of RISO, Inc. All products are
trademarks of their respective companies.
Specifications subject to change without notice.

specifications

function	Color Copying, Faxing, Color Printing, Color Network Scanning
print resolution	Black, Color: 2400 Image Quality, 1200 x 1200 dpi
print speed	Letter (black, color, duplex): Up to 20 pages per minute A4 (black, color, duplex): Up to 19 pages per minute
time to first page (black)	<15 seconds
copy speed	Letter (black, color): Up to 20 pages per minute A4 (black, color): Up to 19 pages per minute
first copy out time	Mono: 18.5 Seconds; color: 24 Seconds
scan resolution, optical	300 x 300 dpi
scan speed (letter)	Letter—black: up to 23 ppm; color: up to 14 ppm A4—black: up to 23 ppm; color: up to 14 ppm
processor	600 MHz
expandable memory options	Yes
memory MFP	Standard: 256 MB; maximum: 512 MB
fax modem speed	33.6 Kbps
scan area, maximum	8.5 x 14 inches (216 x 355 mm)
ADF original input capacity	Up to 50 pages 75 gsm bond
ADF media weight	Maximum: 32 lbs. (120 gsm)
copy quantity	1-999 copies at one time
reduce/enlarge range	25-400%
fax server integration	Biscom FAXCOM, Equisys ZetaFax, Omtool Fax Sr., Captaris RightFax
scan to file	Scan to PC, Scan to FTP Server
document scanning and distribution	RISO Document Solutions Suite
standard ports	USB 2.0 Compatible, Ethernet 10/100BaseTX, 1 Internal Card Slot
optional local ports	Internal RS-232C serial
optional network ports	External 802.11b Wireless
network connectivity	Using Standard Ethernet
paper handling configuration	Standard: 100-Sheet Multipurpose Tray, 500-Sheet Input Tray, 500-Sheet Drawer, Duplex Unit, 250-Sheet Output Bin; Optional: 500-Sheet Drawer, Envelope Feeder, 3,000-Sheet Finisher
paper input capacity	Std: 1100 pages 75 gsm bond. Max: 2100 pages 75 gsm bond
paper output capacity	Std: 250 pages 75 gsm bond. Max: 3250 pages 75 gsm bond
media sizes, supported	A4, A5, Executive, Folio, JIS-B5, Legal, Letter, Statement, 10 Envelope, 7 3/4 Envelope, 9 Envelope, B5 Envelope, C5 Envelope, DL Envelope, Universal
media types, supported	Card Stock, Envelopes, Plain Paper, Transparencies. Refer to the Card Stock & Label Guide
supplies yields	Ships with 6,000*-page black and color Return Program Print Cartridges, 6,000*-page Print Cartridge, 15,000*-page High Yield Print Cartridge *Yield at approximately 5% coverage per color (CMYK)
printer languages (standard)	PCL 6 Emulation, PDF V1.2, 1.3, PostScript 3 Emulation
font selection	2 PCL bitmap fonts, 84 scalable PCL fonts, OCR-A, OCR-B scalable PCL 5e fonts
size (h x w x d)	MFP bundle: 51 x 26.5 x 24 inches (1295 x 673 x 610 mm)
weight (MFP bundle)	190 lbs. (86.4 Kg)
noise level	Idle: 40 dBA; Copying: 59 dBA; Print: 51 dBA; Scan: 54 dBA
engine duty cycle	Maximum: 85,000 one-time monthly usage pages per month
scanner duty cycle	Maximum: 10,000 pages per month

M752
multi-function printer

