benefits

Easy to Use, High Performance Color 11" x 17" MFP

- Large, customizable, color touch screen with intuitive interface
- Fast printer and scanner for maximum productivity with color and mono print speeds of up to 28 ppm and scanner speeds of up to 34 (mono) or 19 (color) duplex page sides per minute
- Time to first print is less than 15 seconds and time to first copy 19 seconds (mono), so users can get jobs in a hurry

Reduce Costs and Optimize Device Utilization with Distributed MFPs

Consolidate your devices (copier, fax, scanner and printer) using one set of supplies for convenience and one machine for productivity, providing excellent cost savings and value for your organization.

Advanced Workflow Solutions

- RISO MFPs, in conjunction with RISO
 Document Solutions Suite applications, simplify business processes with documents on demand, electronic forms, and scan-to-email solutions that are network proven, secure and manageable.
- RISO offers customized solutions to meet business needs for industry specific applications. V e r > c o m p

Versatile 11" x 17" Color MFP

 Handles growth and flexibility with media sizes from 5.5" x 5.5" to 12" x 36" for a variety of applications—posters, signage, banners, and more.



Supported Operating Systems

- Apple Mac OS 8.6 9.x
- Apple Mac OS X

Microsoft Windows

- Microsoft Windows 2000 (Professional/Server/ Advanced Server)
- · Microsoft Windows 95 4.00.950 or later
- Microsoft Windows 98 (2nd edition)
- Microsoft Windows Me
- Microsoft Windows NT (4.00/4.00 Server)
- Microsoft Windows XP (Home, Professional)

- Microsoft Windows 2000 Server Terminal Services, with Citrix MetaFrame 1.8 or XP 1.0
- Microsoft Windows NT 4.0 Terminal Server, with

Citrix®MetaFrame® 1.8 or XP 1.0

Linux

- Red Hat Linux 7.2, 7.3, 8.0

- Compaq (Digital) UNIX 4.0D

- IBM AIX 4.2.1, 4.3.3, 5.1
- SCO OpenServer 5.0.4, 5.0.5, 5.0.6

Novell

- Novell NetWare® 3.x, 4.x, 5.x, 6.x including full

Other

with OS/400® V3R1 or later using OS/400 Host



RISO, Inc.

300 Rosewood Drive Danvers, MA 01923

Tel: 800-876-RISO (ref. 501)

us.riso.com

No part of this document may be reproduced without permission of RISO, Inc. All products are trademarks of their respective companies. Specifications subject to change without notice.

Citrix MetaFrame

trademarks of Citrix Systems, Inc. in the U.S. and other countries

- SuSE 7.2, 7.3, 8.0 Linux

- Compaq Tru64 UNIX 4.0F, 5.1
- HP-UX 10.20, 11.00
- SGI IRIX 6.5.x
- Sun Solaris 2.6, 7, 8, 9
- Sun Solaris x86 2.6, 7, 8
- (SCO) UnixWare 2.1.3, 7.1, 7.1.1

Novell Netware Enterprise Print Services (NEPS) with Lexmark NDPS IP Gateway

- NDS and NDPS support
- Novell® Distributed Print Services™ (NDPS™) 2.0 or later with Lexmark NDPS IP Gateway

- IBM iSeries or IBM AS/400* Systems with TCP/IP Print Transform
- Virtually any platform supporting TCP/IP



©Copyright 2005 RISO, Inc. All rights reserved.

Printed in USA

specifications

function Color Copying, Faxing, Color Printing, Color Network

Scanning

print resolution Black/Color: 2400 Image Quality

Black/Color: Up to 28 ppm; Duplex/Black: Up to 19 ppm print speed (letter)

time to first page (black) <15 seconds

copy speed (black/color) Letter: Up to 28 pages per minute; Mono: 19 Seconds; Color: 27 Seconds first copy out time

scan resolution, optical 600 x 600 dpi

scan speed (A4/letter) Black: Up to 34 ppm; Color: Up to 19 ppm

600 MHz processor expandable memory options Yes

memory MFP Standard: 256 MB; Maximum: 512 MB

modem speed 33.6 Kbps

Maximum: 11.7 x 17 inches (297 x 432 mm) scan area

ADF original input capacity Up to 50 pages 75 gsm bond

ADF maximum media weight 32 lbs. (120 gsm)

copy quantity 1 - 999 copies at one time

25 - 400% reduce/enlarge range

fax server integration Biscom FAXCOM, Equisys ZetaFax, Omtool Fax Sr., Captaris

RightFax

scan to file Scan to PC, Scan to FTP Server document scanning RISO Document Solutions Suite

and distribution

USB 2.0 Compatible, Ethernet 10/100BaseTX. One Internal Card standard ports

Slot

optional local ports Internal RS-232C serial, Internal 1284-C Bidirectional Parallel optional network ports External 802.11b Wireless, Coax/Twinax Adapter for SCS

network connectivity Using Standard Ethernet

100-Sheet Multipurpose Feeder, 550-Sheet Input Tray, paper handling

configuration (standard) 550-Sheet Drawer, Duplex Unit, 100-Sheet Exit Tray, 550-Sheet

Output Bin

paper handling 3,000-Sheet High-capacity Feeder, Heavy Media Input Tray, configuration (optional) 1,100-Sheet Staple Punch Finisher

paper input capacity Standard: 1200 pages 75 gsm bond; Maximum: 4200 pages

75 gsm bond

Standard: 650 pages 75 gsm bond; Maximum: 1650 pages paper output capacity

75 gsm bond

A4, A5, Executive, JIS-B5, Legal, Letter, Super Tabloid, 10 media sizes, supported

Envelope, 7 3/4 Envelope, 9 Envelope, B5 Envelope, C5 Envelope, DL Envelope, 12" x 36" Banner, Universal

media types, supported Card Stock, Envelopes, Plain Paper, Transparencies. Refer to

the Card Stock & Label Guide.

Ships with 8,000*-page black and color Starter Toner supplies yields

> Cartridges. 14,000*-page black and color Toner Cartridges. *Yield at approximately 5% coverage per color (CMYK)

Standard: PCL 6 Emulation, PostScript 3 Emulation printer languages

font selection 156 scalable PostScript fonts, 2 PCL bitmap fonts, 83 symbol

sets in PCL 6 emulation, 84 scalable PCL fonts

size (H x W x D) 46 x 57 x 26 inches (1168 x 1448 x 660 mm)

weight 396 lbs.(180 Kg)

Idle: 47 dBA; Copying: 57 dBA; Print: 56 dBA; Scan: 50 dBA noise level engine duty cycle Maximum: Based on one month usage, 100,000 pages/month

scanner duty cycle Maximum: 10,000 pages/month

certifications FCC Class A, UL 60950, CSA, ICES Class A, CS03, IEC 320-1



