

# P634

laser printer

## b e n e f i t s

### Product Overview

The RISO P634 offers flexibility and performance in a variety of printing applications. With a 45 ppm speed, 500 MHz processor, and less than 9 seconds to the first page, the P634 can easily handle applications where fast response and overall speed are important.

- Up to 45 ppm letter, 43 ppm A4
- Time to first page <8.5 seconds
- 500 MHZ processor
- 80MB RAM standard
- Network standard

### Versatile Options

The RISO P634's easily expandable, modular paper-handling options and easy-to-install supplies increase user effectiveness. With a wide range of options such as StapleSmart finishing and mailbox options, the P634 is the ideal printer for workgroups.

### Designed for Specialized Applications

The P634 is designed to handle many specialized applications, with built-in pdf printing and standard bar code and Optical Character Recognition (OCR) fonts. New multi-function options offer affordability and reliability while adding the convenience of copy, fax, and color network scanning capabilities. The RISO P634 is the ideal printer for tailored printing solutions regardless of the size of your organization.



## Supported Operating Systems

### Apple

- Apple Mac OS 8.6 - 9.x
- Apple Mac OS X

### Microsoft Windows

- Microsoft Windows 2000 (Professional/Server/Advanced Server)
- Microsoft Windows 95 4.00.950 or later
- Microsoft Windows 98 (2nd edition)
- Microsoft Windows Me
- Microsoft Windows NT (4.00/4.00 Server)
- Microsoft Windows XP (Home, Professional)

### Novell

- Novell Netware Enterprise Print Services (NEPS) with Lexmark NDPS IP Gateway
- Novell NetWare® 3.x, 4.x, 5.x, 6.x including full NDS and NDPS support
- Novell® Distributed Print Services™ (NDPS™) 2.0 or later with Lexmark NDPS IP Gateway

### Linux

- Red Hat Linux 7.2, 7.3, 8.0
- SuSE 7.2, 7.3, 8.0 Linux

### UNIX

- Certified Solaris Ready by Sun Microsystems
- Compaq (Digital) UNIX 4.0D
- Compaq Tru64 UNIX 4.0F, 5.1
- HP-UX 10.20, 11.00
- IBM AIX 4.2.1, 4.3.3, 5.1
- SCO OpenServer 5.0.4, 5.0.5, 5.0.6
- SGI IRIX 6.5.x
- Sun Solaris 2.6, 7, 8, 9
- Sun Solaris x86 2.6, 7, 8
- (SCO) UnixWare 2.1.3, 7.1, 7.1.1

### Other

- IBM iSeries or IBM AS/400® Systems with TCP/IP with OS/400® V3R1 or later using OS/400 Host Print Transform
- Virtually any platform supporting TCP/IP

### Citrix MetaFrame

- Microsoft Windows 2000 Server Terminal Services, with Citrix MetaFrame 1.8 or XP 1.0
- Microsoft Windows NT 4.0 Terminal Server, with Citrix® MetaFrame® 1.8 or XP 1.0

Citrix, MetaFrame and MetaFrame XP are registered trademarks or trademarks of Citrix Systems, Inc. in the U.S. and other countries.



### RISO, Inc.

300 Rosewood Drive  
Danvers, MA 01923  
Tel: 800-876-RISO (ext. 501)  
www.riso.com

©Copyright 2003 RISO, Inc. All rights reserved. No part of this document may be reproduced without permission of RISO, Inc. All products are trademarks of their respective companies. Specifications subject to change without notice.

Printed in USA

# s p e c i f i c a t i o n s

<b>Print Technology</b>	Monochrome laser
<b>Print Resolution, Black</b>	1200 Image Quality, 1200 x 1200, 300 x 300, 600 x 600 dpi
<b>Print Speed</b>	Letter, black: Up to 45 pages per minute A4, black: Up to 43 pages per minute
<b>Time to First Page (black)</b>	< 8.5 seconds
<b>Processor</b>	500 MHz
<b>Memory network model</b>	Standard: 80 MB; Expandable Memory; Maximum: 336 MB
<b>Paper Handling Configuration (Standard)</b>	500-Sheet Input Tray, 100-Sheet Multipurpose Feeder, 500-Sheet Output Bin
<b>Paper Handling Configuration (Optional)</b>	250-Sheet Drawer, 500-Sheet Drawer, 2,000-Sheet Drawer, Envelope Feeder, 500-Sheet Duplex Unit, StapleSmart Finisher, 5-Bin Mailbox, 1,850-Sheet High-capacity Output Stacker, 650-Sheet Output Expander
<b>Media Sizes, Supported</b>	A4 (8.27" x 11.7" or 210mm x 297mm), A5 (5.83" x 8.27" or 148mm x 210mm), Executive (7.25" x 10.5" or 184mm x 267mm), Folio (8.5" x 13" or 216mm x 330mm), JIS-B5 (7.17" x 10.12" or 182mm x 257mm), Legal (8.5" x 14" or 216mm x 355mm), Letter (8.5" x 11" or 216mm x 279mm), Statement (5.5" x 8.5" or 140mm x 216mm), B5 Envelope (6.93" x 9.84" or 176mm x 250mm), C5 Envelope (6.38" x 9.02" or 162mm x 229mm), DL Envelope (4.33" x 8.66" or 110mm x 220mm), 7 3/4 Envelope (3.875" x 7.5" or 98.4mm x 190.5mm), 9 Envelope (3.875" x 8.9" or 98.4mm x 225.4 mm), 10 Envelope (4.125" x 9.5" or 105mm x 241mm), Universal
<b>Media Types, Supported</b>	Plain Paper, Transparencies, Envelopes, Card Stock, Dual Web Labels, Integrated Labels, Paper Labels, Polyester Labels, Vinyl Labels
<b>Paper Input Capacity</b>	Standard: 600 pages 20 lb or 75 gsm bond; maximum: 4100 pages 20 lb or 75 gsm bond
<b>Paper Output Capacity</b>	Standard: 500 pages 20 lb or 75 gsm bond; maximum: 3000 pages 20 lb or 75 gsm bond
<b>Envelope Capacity</b>	85
<b>Supplies Yields</b>	Ships with 21,000*-page Use and Return Print Cartridge. *Yield at approximately 5% coverage
<b>Standard Ports</b>	USB, Ethernet 10/100BaseTX. Two Internal Card Slots
<b>Optional Local Ports</b>	Internal 1284-B Bidirectional Parallel, Internal RS-232C serial
<b>Optional Network Ports</b>	External 802.11b Wireless, Coax/Twinax Adapter for SCS
<b>Network Connectivity</b>	Using Standard Ethernet
<b>Additional Products</b>	Bar Code Printing, Custom Business Forms, IBM Mainframe and AS/400 Printing, Internet Printing, Local Printing, Management and Installation, Network Printing, SAP Printing
<b>Printer Languages (Std)</b>	PCL 6 Emulation, PDF V1.2, 1.3, Personal Printer Data Stream (PPDS), PostScript 3 Emulation
<b>Font Selection</b>	158 scalable PostScript fonts, 84 scalable PCL font, 2 PCL bitmap fonts, 39 scalable PPDS fonts, 5 PPDS bitmap fonts, OCR-A, OCR-B scalable PCL 5e fonts
<b>Bar Code Fonts</b>	3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide
<b>Printable Area</b>	To within 0.167 in. (4.2 mm) of the top, bottom, right, left edges
<b>Size (H x W x D)</b>	16 inches x 17.2 inches x 20.2 inches (406 x 436 x 513 mm)
<b>Weight</b>	41.5 lbs. (19 Kg)
<b>Acoustics</b>	Idle: 34 dBA; Operating: 55 dBA
<b>Duty Cycle, Maximum</b>	225,000 pages per month
<b>Certifications</b>	FCC Class A, UL 60950 3rd Edition, U.S. FDA, IEC 320-1, CSA, ICES Class A, Energy Star

P634  
laser printer



Item #MC8196